

SIMATIC THIN CLIENT (HARDWARE) 15" TOUCH, THIN CLIENT, 15" TFT DISPLAY, 64K COLORS, CLIENT: SMARTACCESS, RDP, WEB



General information	
Customer-specific configuration	No
Display	
Design of display	TFT
Screen diagonal	15.1 in
Color display	Yes
Number of colors	65 536
Resolution (pixels)	
• Horizontal image resolution	1 024 Pixel
• Vertical image resolution	768 Pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Control elements	Touch screen
Keyboard fonts	
• System keys	No
• alphanumeric keyboard	No
Touch operation	

<ul style="list-style-type: none"> • Design as touch screen 	Yes; analog, resistive
Connection type	
<ul style="list-style-type: none"> • Connection for mouse/keyboard/barcode reader 	USB / USB
Installation type/mounting	
maximum permissible angle of inclination without external ventilation	35°
Supply voltage	
Type of supply voltage	DC
Input current	
Starting current inrush I ² t	1 A ² ·s
Processor	
Processor type	ARM, 266 MHz
Memory	
Type of memory	Flash / RAM
Interfaces	
Interfaces/bus type	1 x Ethernet (RJ45)
Number of RS 485 interfaces	0
Number of USB interfaces	1
With software interfaces	No
Industrial Ethernet	
<ul style="list-style-type: none"> • Industrial Ethernet interface • Industrial Ethernet status LED 	1 x Ethernet (RJ45) 2
Protocols	
Supports protocol for PROFINET IO	Yes
PROFIsafe	No
PROFIBUS	No
Protocols (Ethernet)	
<ul style="list-style-type: none"> • TCP/IP 	Yes
WEB characteristics	
<ul style="list-style-type: none"> • HTTP • HTML • XML • CSS • JavaScript 	Yes Yes Yes Yes Yes
Protocols (terminal link)	
<ul style="list-style-type: none"> • Sm@rtServer • RDP 	Yes Yes
Further protocols	
<ul style="list-style-type: none"> • EtherNet/IP 	No

- MODBUS
- other bus systems

No

Yes

EMC

Emission of radio interference acc. to EN 55 011

- Limit class A, for use in industrial areas

Yes; EN 61000-6-4, interference emission: Intended for use in industrial areas.

Degree and class of protection

IP (at the front)

IP54

NEMA (front)

NEMA 12 (when installed)

IP (rear)

IP20

Standards, approvals, certificates

Certifications

CE, cULus, C-TICK, NEMA 12 (when installed: IP54, enclosure type 12; optional IP65, enclosure type 4X/type 12 (6AV6671-6AP00-0AX0))

cULus

Yes

EMC

The product is designed for use in industrial environments. When used in residential areas, the emission of radio interference according to limit class B of EN 55011 must be ensured. For further information refer to the user documentation

Suitable for safety functions

No

Ambient conditions

Ambient temperature during operation

- min.

0 °C

- max.

50 °C

Ambient temperature during storage/transportation

- min.

-20 °C

- max.

60 °C

Relative humidity

- Operation, max.

85 %; Storage

Configuration

Recipe management

No

Languages

Online languages

- Number of online/runtime languages

2

Peripherals/Options

Additional software components loadable

No

Dimensions

Width of the housing front

400 mm

Height of housing front

310 mm

Mounting cutout, width

368 mm

Mounting cutout, height	290 mm
Overall depth	65 mm
Weights	
Weight (without packaging)	3.6 kg
last modified:	08/12/2017