

SIMATIC S7-300, Front connector for signal modules with spring-loaded contacts, 20-pole



General information

Product type designation Front connector

Ambient conditions

Ambient temperature during operation

- min. 0 °C
- max. 60 °C

Ambient temperature during storage/transportation

- min. -40 °C
- max. 70 °C

Accessories

belongs to product S7-300

Connection method

Connection I/O signals

- Connection method Spring terminals
- Number of lines per connection 1; or combination of 2 conductors of up to 1.5 mm² (total) in a shared ferrule

Conductor cross-section in mm²

- Connectable cable cross-sections for massive cables, min.
- Connectable cable cross-sections for massive cables, min.
- Connectable cable cross-sections for flexible cables without end sleeve, min.
- Connectable cable cross-sections for flexible cables without end sleeve, max.
- Connectable cable cross-sections for flexible cables with end sleeve, min.
- Connectable cable cross-sections for flexible cables with end sleeve, max.

0.25 mm²
 1.5 mm²
 0.25 mm²
 1.5 mm²
 0.25 mm²
 1.5 mm²

Conductor cross-section acc. to AWG

- Connectable cable cross-sections for massive cables, min.
- Connectable cable cross-sections for massive cables, min.
- Connectable cable cross-sections for flexible cables without end sleeve, min.
- Connectable cable cross-sections for flexible cables without end sleeve, max.
- Connectable cable cross-sections for flexible cables with end sleeve, min.
- Connectable cable cross-sections for flexible cables with end sleeve, max.

24
 16
 24
 16
 24
 16

Wire end processing

- Stripped length of cables, min.
- Stripped length of cables, max.
- End sleeve acc. to DIN 46228 without plastic sleeve
- End sleeve acc. to DIN 46228 with plastic sleeve

6 mm
 6 mm
 Design A, 5 mm to 7 mm long
 Design E, up to 6 mm long

Dimensions

Width	23 mm
Height	131 mm
Depth	36 mm

Weights

Weight, approx.	61 g
-----------------	------

last modified: 04/06/2018